


LARGE CAPACITY ELECTRIC CHAIN HOIST





SPECIFICATIONS - LARGE CAPACITY ELECTRIC CHAIN HOIST

Model	W.L.L. (mt)	Standard Lift (ft)	Lifting Speed (ft/min)		Lifting Motor Output (H.P.)	Trolley Min. Radius (in)	Load Chain (mm) x Number of Falls
			50 Hz	60 Hz			
DA-15	15	13	5.9	6.8	4.62 x 2	70.8	11.2 x 6
DA-20	20	13	4.2	5.2	4.62 x 2	81.4	11.2 x 8
DA-30	30	13	2.9	3.2	4.62 x 2	98.4	11.2 x 12
DA-50	50	13	1.6	1.9	4.62 x 2	114	11.2 x 22

Electric Chain Hoist with Motorized Trolley

Model	W.L.L. (mt)	Standard Lift (ft)	Traversing Speed (ft/min)		Traversing Motor Output (H.P.)	Trolley Min. Radius (in)	Load Chain (mm) x Number of Falls
			50 Hz	60 Hz			
DAM-15	15	13	32.8	39.3	2.04	-	11.2 x 6
DAM-20	20	13	32.8	39.3	2.04	-	11.2 x 8

*Larger capacities available upon request

Electric Chain Hoist with Geared Trolley

Model	W.L.L. (mt)	Standard Lift (ft)	Trolley Min. Radius (in)	Load Chain (mm) x Number of Falls
DAG-15	15	13	275.5	11.2 x 6
DAG-20	20	13	275.5	11.2 x 8

*Larger capacities available upon request

